

WAF1-5203-04-00B

# 19" 4/3U WALL-MOUNTED CABINET



## PRODUCT FEATURES:

- Two mounting rails, vertical 4U and horizontal 3U,
- Mesh plate located on the rear wall (using an M6 screw to attach components to it),
- Cable holes in the top and bottom panels unscrewed,
- Knock-out holes in the rear wall of the cabinet,
- Double-sided opening doors,
- Ventilation holes in the upper and lower panels and side walls,

## PRODUCT SPECIFICATION:

Type of cabinet	Wall mount
Size	19"
ICT height	4 U
Working depth	143 mm
Front door type	Metal
Maximum front door opening angle	220 °
Maximum static load	60 kg
Thermostat	No
LCD panel	No
RAL color	RAL9004
Weatherproof rating	IP20
Front door thickness	1 mm
Upper & lower panel thickness	1 mm
Side panel thickness	1 mm
Mounting rails thickness	1,5 mm
Frame thickness	1,2 mm
Other elements sheet thickness	1 mm
Depth	200 mm
Width	540 mm
Height	400 mm
Weight	9,3 kg
Standard	ANSI/EIA RS-310-D, DIN 41491/PART 1, DIN 41494/PART 7, ETSI, IEC297-2:1982
Grounding Details	Front door, Bottom panel
Included Accessories	User Manual, Grounding cable, M6 screws, DIN rail TS-35, Front lock

